

1B



Specifications

| | |
|------------------------|----------------------------------|
| CAPACITY | 5kg、6kg、10kg、12kg、15kg、20kg、50kg |
| COMPREHENSIVE ERROR | 0.03 |
| OUTPUT SENSITIVITY | 1.8 ± 0.1 mV/V |
| NONLINEARITY | $\pm 0.02\%$ F.S. |
| REPEATABILITY | $\pm 0.02\%$ F.S. |
| HYSTERESIS | $\pm 0.03\%$ F.S. |
| CREEP | $\pm 0.03\%$ F.S.5min |
| TEMP. EFFECT ON ZERO | $\pm 0.3\%$ F.S./10°C |
| TEMP. EFFECT ON OUTPUT | $\pm 0.03\%$ F.S./10°C |
| ZERO OUTPUT | ± 0.1 mV/V |
| INPUT RESISTANCE | $1055 \pm 10 \Omega$ |
| OUTPUT RESISTANCE | $1000 \pm 10 \Omega$ |
| INSULATION RESISTANCE | > 3000 M Ω (50V) |
| EXCITATION VOLTAGE | < 10 V |
| OPERATION TEMP. RANGE | -10~+40°C |
| OVERLOAD CAPACITY | 150% F.S. |
| RECOMMENDED USE | PORTABLE SCALES |

Dimensions mm (inch)

